PRODUCT RECOMMENDATION

WACKER NEUSON TRACKED EXCAVATORS 75Z3 YANMAR 4TNV98-ZVNS TIER 3 (AH00611 ->)

ENGINE Yanmar 4TNV98-ZVNS
Capacity: 10,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 99 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus Biosynth 46	**Perlus H 46**	

Change every 1000 hours/ 12 months

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

WACKER NEUSON TRACKED EXCAVATORS 75Z3 YANMAR 4TNV98-ZVNS TIER 3 (AH00611 ->)

COOLING SYSTEM
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Change every 1000 hours/ 12 months

SWING RING GEARING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2	**MP Lithep Grease EP 2**

TRAVEL REDUCTION UNIT
Capacity: 1,3 liter (each)

USE	CLIMATE
Normal, <- 10/2006	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Change every 1000 hours/ 12 months

USE	CLIMATE
Normal, 10/2006 ->	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Change every 1000 hours/ 12 months

USE	CLIMATE
Initial service, <- 10/2006	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Change every 50 hours

USE	CLIMATE
Initial service, 10/2006 ->	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367