

WERKLUST WHEELED LOADERS WG WG 17E CUMMINS QSB 4.5

**ENGINE** Cummins QSB4.5

Capacity: 16,4 liter, Filter capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40*Change every 250 hours***DIFFERENTIAL FRONT** ZF MT-3065 CK

Capacity: 24,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

PRODUCT RECOMMENDATION 3

Unigear LS GL-3/GL-5 85W-140*Check every 100 hours, change every 1000 hours***DIFFERENTIAL REAR** ZF MT-3065 BKV

Capacity: 24,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

PRODUCT RECOMMENDATION 3

Unigear LS GL-3/GL-5 85W-140*Check every 100 hours, change every 1000 hours***TRANSMISSION POWERSHIFT** ZF 4WG130 4/3

Capacity: 17 liter (Dry fill), Capacity: 9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 1000 hours*

WERKLUST WHEELED LOADERS WG WG 17E CUMMINS QSB 4.5



HYDRAULIC SYSTEM

Capacity: 196 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Change every 2000 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

COOLING SYSTEM

Capacity: 29 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.