PRODUCT RECOMMENDATION

WILLE ARTICULATED LOADERS 455B
DETROIT D754 TE3

ENGINE D754 TE3
Capacity: 7-10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 300 hours/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 150 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 50 hours

DIFFERENTIAL FRONT
Capacity: 7,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

DIFFERENTIAL REAR
Capacity: 7,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

HUB REDUCTIONS FRONT
Capacity: 0,35 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

WILLE ARTICULATED LOADERS 455B DETROIT D754 TE3

HUB REDUCTIONS REAR
Capacity: 0,35 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

TRANSMISSION HYDROSTATIC
Capacity: 0,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM
Capacity: 60 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	**Perlus AF 68**	

COOLING SYSTEM
Capacity: 5 liter (Engine only), Capacity: 15 liter (Total system volume)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367