

WIRTGEN COLD MILLING MACHINES W500**06.05.0430 -> 06.05.1412 (2004 AND AFTER)**

ENGINE Iveco 8045 SU
Capacity: 11,5 liter

| USE | | CLIMATE |
|-----------------------------|-------------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 |

Check every 10 hours, change every 250 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|-------------------------------|-----------------------------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 |

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 180 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |

Check every 10 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|---------------------------|--------------------------|---------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Perlus Biosynth 46 | Perlus H 46 | Perlus Biosynth 32 |

Check every 10 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 22 | | |

Check every 10 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

Check every 10 hours

WIRTGEN COLD MILLING MACHINES W500**06.05.0430 -> 06.05.1412 (2004 AND AFTER)****COOLING SYSTEM ENGINE**

Capacity: 20 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

*Check every 10 hours, change every 12 months***TRAVEL REDUCTION UNIT**

Capacity: 0,8 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 50 hours, change every 500 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.