

# YALE FORKLIFT TRUCKS, DIESEL GDP 060 ECPB (1979-1982)

**ENGINE** Perkins

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Change every 1 months/ 200 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Change every 50 hours/ 1 week***TRANSMISSION AUTOMATIC** Eaton SY

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D****HYDRAULIC SYSTEM POWER STEERING**

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Perlus H 68***Change every 6 months/ 1200 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 6 months/ 1200 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Perlus H 22***Change every 6 months/ 1200 hours*

# YALE FORKLIFT TRUCKS, DIESEL GDP 060 ECPB (1979-1982)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## GREASE POINTS/NIPPLES BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*