## YALE FORKLIFT TRUCKS, ELECTRIC - STANDARD EXCEL RANGE ERP 050 DL



| TRANSMISSION             |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Gearlube GL-5 85W-140    |          |

| HYDRAULIC SYSTEM                   |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Perlus H 32                        |          |
| Change every 2000 hours/ 12 months | '        |

| HYDRAULIC BRAKE SYSTEM             |          |  |
|------------------------------------|----------|--|
| USE                                | CLIMATE  |  |
| Normal                             | Moderate |  |
| PRODUCT RECOMMENDATION 1           |          |  |
| Drauliquid DOT 3                   |          |  |
| Change every 2000 hours/ 12 months |          |  |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal                   |                          | Moderate                 |
| USE                      |                          | CLIMATE                  |

## YALE FORKLIFT TRUCKS, ELECTRIC - STANDARD EXCEL RANGE ERP 050 DL



| GREASE POINTS/NIPPLES CHANNEL FACES |                          |                          |
|-------------------------------------|--------------------------|--------------------------|
| USE                                 |                          | CLIMATE                  |
| Normal                              |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease                       | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| GREASE POINTS/NIPPLES CONTROL LINKAGE |                          |                          |
|---------------------------------------|--------------------------|--------------------------|
| USE                                   |                          | CLIMATE                  |
| Normal                                |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease                         | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| GREASE POINTS/NIPPLES ELEC | TRIC MOTOR BEARINGS      |          |  |
|----------------------------|--------------------------|----------|--|
| USE                        |                          | CLIMATE  |  |
| Normal                     |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |  |
| Labora Grease              | Multi Purpose Grease 3   |          |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.