## YALE FORKLIFT TRUCKS, LPG/PETROL GLP 15 AE



ENGINE	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
HDX 40	
Change every 1 months/ 200 hours	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
HDX 30	
Change every 1 months/ 200 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
HDX 20W-20	
Change every 1 months/ 200 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
HDX 10W	
Change every 1 months/ 200 hours	
USE	CLIMATE
Initial service	Tropical
PRODUCT RECOMMENDATION 1	
HDX 40	
Change every 50 hours/ 1 week	
USE	 CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
HDX 30	
Change every 50 hours/ 1 week	
USE	 CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
HDX 20W-20	
Change every 50 hours/ 1 week	

## YALE FORKLIFT TRUCKS, LPG/PETROL GLP 15 AE



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 50 hours/ 1 week		

DIFFERENTIAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 12 months/ 2400 hour	rs	

TRANSMISSION AUTOMATIC Yale	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Change every 6 months/ 1200 hours

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 6 months/ 1200 hours	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 6 months/ 1200 hours	·

## YALE FORKLIFT TRUCKS, LPG/PETROL GLP 15 AE



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES BEAF	RINGS	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.