PRODUCT RECOMMENDATION

YANMAR TRACKED EXCAVATORS VIO17

ENGINE Yanmar 3TNV70
Capacity: 3,2 liter, Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**

Change every 250 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 250 hours

HYDRAULIC SYSTEM
Capacity: 26 liter, Capacity: 16,5 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 1000 hours

COOLING SYSTEM
Capacity: 2,7 liter (Radiator), Capacity: 0,4 liter (Subtank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Change every 24 months

TRAVEL REDUCTION UNIT
Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367