

YANMAR TRACKED EXCAVATORS VIO20-3

YANMAR 3TNE74 (2003-2006)

**ENGINE** Yanmar 3TNE74

Capacity: 3,5 liter, Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

HYDRAULIC SYSTEM

Capacity: 26 liter (Hydraulic tank), Capacity: 39 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

COOLING SYSTEM

Capacity: 2,9 liter (Radiator), Capacity: 0,4 liter (Subtank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

TRAVEL REDUCTION UNIT

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.