

# YANMAR TRACKED EXCAVATORS VIO33U (2011-2015)

**ENGINE** Yanmar 3TNV82

Capacity: 4,4 liter, Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40***Change every 250 hours*

USE	CLIMATE
Normal	Cold

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 250 hours***HYDRAULIC SYSTEM**

Capacity: 35 liter (Hydraulic tank), Capacity: 52 liter (System)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 46***Change every 1000 hours***COOLING SYSTEM**

Capacity: 3,1 liter (Radiator), Capacity: 0,4 liter (Subtank)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

## PRODUCT RECOMMENDATION 2

**Coolant SP 12**

## PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Change every 24 months***TRAVEL REDUCTION UNIT**

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.