HYUNDAI (BEIJING) AZERA HG AZERA 3.0 V6 GDI (199 KW) (2011 AND AFTER)



ENGINE Lambda G6DG Capacity: 5,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Presteza MSP 5W-30	Emperol 10W-40	

Change every 5000 km/ 6 months

TRANSAXLE AUTOMATIC 6/1 Capacity: 7,8 liter	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

Change every 90000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,7-0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING Capacity: 0,9 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 SP Fluid 3013	

HYUNDAI (BEIJING) AZERA HG AZERA 3.0 V6 GDI (199 KW) (2011 AND AFTER)



COOLING SYSTEM Capacity: 8,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Change every 40000 km/ 24 months			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Change every 200000 km/ 120 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.