BUICK (SGM) EXCELLE EXCELLE GT 1.5 (2015 AND AFTER)



ENGINE L2B Capacity: 4 liter (Service fill)	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 0W-20	

Change every 5000 km/ 6 months

TRANSAXLE AUTOMATIC 6/1 Capacity: 8,2 liter (Service fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
01 000001	

Change every 80000 km

TRANSAXLE MANUAL 5/1 Capacity: 2 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 10000 km/ 6 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 10000 km/ 6 months, change every 30000 km/ 24 months

COOLING SYSTEM Capacity: 6,2 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 10000 km/ 6 months, change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the BUICK (SGM) EXCELLE EXCELLE GT 1.5 (2015 AND AFTER)



information contained herein is subject to changes without notification.