BUICK (SGM) EXCELLE EXCELLE (HRV) 1.8 (2003-2008)



ENGINE T18SED
Capacity: 4 liter

USE
Normal

PRODUCT RECOMMENDATION 1
Duranza LSP 5W-30

CLIMATE
Moderate

PRODUCT RECOMMENDATION 2
Asyntho 5W-30

Check every 1000 km, change every 10000 km/6 months

USE CLIMATE
Severe Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2
Duranza LSP 5W-30 Asyntho 5W-30

Change every 5000 km/3 months

TRANSAXLE AUTOMATIC ZF 4HP16 4/1 Capacity: 6,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Check every 5000 km/ 3 months	

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

Change every 60000 km

TRANSAXLE MANUAL 5/1 Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 10000 km/ 6 months	•	·

BUICK (SGM) EXCELLE EXCELLE (HRV) 1.8



(2003-2008)

HYDRAULIC BRAKE/CLUTCH SYSTE Capacity: 0,5 liter	М	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 5000 km/ 3 months, chang	e every 30000 km/ 18 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 15000 km		

POWER STEERING Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 10000 km/ 6 months	,	

COOLING SYSTEM Capacity: 7,4 liter			
use Normal		сымате Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Change every 240000 km/ 60 mon	ths	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.