

BUICK (SGM) EXCELLE EXCELLE XT 1.6

SGM7160MTB/SGM7160ATB (2010-2011)



ENGINE LDE
Capacity: 4,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

Check every 3000 km/ 1 months, change every 5000 km/ 6 months

TRANSAXLE AUTOMATIC 6/1
Capacity: 8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Change every 160000 km

TRANSAXLE MANUAL 5/1
Capacity: 1,8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Check every 10000 km/ 6 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

COOLING SYSTEM
Capacity: 6,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15

PRODUCT RECOMMENDATION 2

Coolant SP 15+

Change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

BUICK (SGM) EXCELLE EXCELLE XT 1.6 SGM7160MTB/SGM7160ATB (2010-2011)



information contained herein is subject to changes without notification.