

PRODUCT RECOMMENDATION

# BYD L3 L3 1.5 (80 KW) QCJ7153A5/A6/A7, BYD7153A/A1 (2008 AND AFTER)



## ENGINE BYD473QE

Capacity: 3,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    |

*Change every 5000 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    |

*Change every 3000 km*

## TRANSAXLE DCT 6DT25 6/1

Capacity: 1,7-1,8 liter

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>Gearlube GL-4 80W</b> |  |

*Change every 55000 km*

| USE          | CLIMATE  |
|--------------|----------|
| Subsequently | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>Gearlube GL-4 80W</b> |  |

*Check every 60000 km*

PRODUCT RECOMMENDATION

# BYD L3 L3 1.5 (80 KW) QCJ7153A5/A6/A7, BYD7153A/A1 (2008 AND AFTER)



## TRANSAXLE MANUAL 5/1

Capacity: 2,1 liter

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| First change only        |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

Change every 8000 km/ 3 months

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Normal, first inspection |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

Check every 3000 km

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Subsequently             |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

Check every 10000 km/ 6 months, change every 20000 km/ 12 months

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,8-1 liter

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Check every 5000 km/ 3 months, change every 20000 km/ 12 months

## POWER STEERING

Capacity: 1 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

Check every 10000 km/ 6 months, change every 20000 km/ 12 months

# BYD L3 L3 1.5 (80 KW) QCJ7153A5/A6/A7, BYD7153A/A1 (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 6,8 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 10000 km/ 6 months, change every 20000 km/ 12 months

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Initial service               |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 3000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.