BYD S6 S6 2.0 QCJ6480S/S5 (2011 AND AFTER)



| ENGINE BYD483QB Capacity: 3,3 liter, Filter capacity: 0,3 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Asyntho 5W-30 | Emperol 10W-40 | |
| Change every 5000 km/ 6 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Asyntho 5W-30 | Emperol 10W-40 | |
| Change every 3000 km | | |

| USE | | CLIMATE |
|--------------------------------|--------------------------|--------------------------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |
| Change every 8000 km/ 6 months | | |
| JSE | | CLIMATE |
| Normal, first inspection | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |
| Check every 3000 km | | |
| JSE | | CLIMATE |
| Subsequently | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

BYD S6 S6 2.0 QCJ6480S/S5 (2011 AND AFTER)



| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8-1 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |
| Check every 5000 km/ 3 months, change | every 40000 km/24 months | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |
| Change every 15 months | | |

| POWER STEERING Capacity: 1,1 liter | | |
|------------------------------------|-------------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 2032 | ATF Almirol | |
| Check every 5000 km/ 3 months, ch | ange every 40000 km/24 months | · |
| USE | | CLIMATE |

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 2032 | ATF Almirol | |
| Change every 20000 km | , | , |

| COOLING SYSTEM Capacity: 6,4-7,9 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| 01 1 400001 10 11 | | |

Check every 10000 km/6 months, change every 40000 km/24 months

AIRCONDITIONING SYSTEM Capacity: 550-650 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.