SUZUKI (CHANG'AN) SX4 S-CROSS SX4 S-CROSS 1.6 (2013 AND AFTER)



| Normal | | Moderate |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 0W-20 | Helar SP LL-03 5W-30 | Presteza MSP 5W-30 |

Change every 2500 km/4 months

| TRANSAXLE CVT 1/1 Capacity: 6,7 liter | | |
|--|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4016 | | |

| USE | CLIMATE |
|----------------------------------|----------|
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear 1081 | |
| Change every 30000 km/ 24 months | |
| USE | CLIMATE |
| Severe | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear 1081 | |
| Change every 10000 km | |
| USE | CLIMATE |
| Initial service | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear 1081 | |
| Check every 1000 km | |
| USE | CLIMATE |
| First change only, severe | Moderate |

Change every 15000 km/ 12 months

SUZUKI (CHANG'AN) SX4 S-CROSS SX4 S-CROSS 1.6 (2013 AND AFTER)



| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and ma | x.) | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Change every 30000 km/ 24 months | · | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Change every 36 months | | |

| HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and m | nax.) | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Change every 30000 km/24 months | | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Change every 36 months | · | |

| COOLING SYSTEM Capacity: 6,1 liter (with CVT transmission), Capacity: 5,8 liter (with manual transmission) | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 14+ | Coolant -38 Organic NF | | |
| Change every 45000 km/ 36 month | ns | | |
| USE | | CLIMATE | |
| First change only | | Moderate | |

| First change only | | Moderate |
|---------------------------------------|--------------------------|----------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 14+ Coolant -38 Organic NF | | |
| Change every 10000 km | | |

Change every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

SUZUKI (CHANG'AN) SX4 S-CROSS SX4 S-CROSS 1.6 (2013 AND AFTER)



information contained herein is subject to changes without notification.