CHANG'AN BENNI F3 BENNI F3 1.3 (2010 AND AFTER)



ENGINE GL474Q2 Capacity: 3,6 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Bi-Turbo 15W-40			
Change every 5000 km/ 6 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Asyntho 5W-30	Emperol 10W-40		
Change every 5000 km/ 6 months			

TRANSAXLE MANUAL 5/1 Capacity: 2,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-4 80W-90	
Change every 10000 km/ 6 months	'

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 10000 km/ 6 months				

POWER STEERING				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Matic 2032	ATF Almirol			

CHANG'AN BENNI F3 BENNI F3 1.3 (2010 AND AFTER)



COOLING SYSTEM Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.