

# CHANG'AN CS75 CS75 2.0 (2014 AND AFTER)



**ENGINE** JL486Q5  
Capacity: 4,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>

*Change every 5000 km/ 3 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>

*Change every 3000 km/ 3 months*

## TRANSAXLE AUTOMATIC 6/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Matic 4036</b>	

## TRANSAXLE MANUAL 6/1

Capacity: 2-2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,78 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

*Change every 40000 km/ 24 months*

# CHANG'AN CS75 CS75 2.0 (2014 AND AFTER)


**COOLING SYSTEM**

Capacity: 6,8-7,4 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1**
**Coolant SP 15+**
**PRODUCT RECOMMENDATION 2**
**Coolant SP 12**

*Check every 10000 km/ 6 months, change every 20000 km/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*