

**CHERY V5 V5 2.4 16V (2010-2015)**

**ENGINE 4G64**  
Capacity: 3,5-4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 15000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 5000 km*

**TRANSAXLE AUTOMATIC 4/1**  
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026***Check every 5000 km, change every 100000 km*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**  
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 50000 km/ 24 months*

**POWER STEERING**  
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol***Check every 15000 km*

**CHERY V5 V5 2.4 16V (2010-2015)****COOLING SYSTEM**

Capacity: 7,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Change every 40000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*