

# CITROËN (DONGFENG) PICASSO (BIJIASUO) PICASSO (BIJIASUO) 2.0 (2001 AND AFTER)

**ENGINE** PSA EW10J4 (RFN)

Capacity: 4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 10000 km/ 12 months***TRANSAXLE MANUAL** 5/1

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 5015**

PRODUCT RECOMMENDATION 2

**Gearlube RPC 75W-80***Check every 60000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 60000 km/ 24 months***POWER STEERING**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

PRODUCT RECOMMENDATION 3

**ATF Dexron II-D***Change every 10000 km/ 12 months*

# CITROËN (DONGFENG) PICASSO (BIJIASUO) PICASSO (BIJIASUO) 2.0 (2001 AND AFTER)

**COOLING SYSTEM**

Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Change every 60000 km/ 24 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*