

# FENGSHEN (DONGFENG) L60 L60 1.8 WFZ (2015 AND AFTER)

**ENGINE EC8**

Capacity: 4,1 liter (Dry fill), Capacity: 3,5 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Presteza MSP 0W-30</b>	<b>Duranza LSP 5W-30</b>

*Change every 7500 km/ 6 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Presteza MSP 0W-30</b>	<b>Duranza LSP 5W-30</b>

*Check every 2500 km/ 3 months***TRANSAXLE AUTOMATIC 6/1**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Matic 2032</b>	

*Check every 60000 km/ 48 months, change every 90000 km/ 72 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Gear 5015</b>	

*Change every 60000 km/ 48 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,83 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

*Check every 7500 km/ 6 months, change every 30000 km/ 24 months*

# FENGSHEN (DONGFENG) L60 L60 1.8 WFZ (2015 AND AFTER)



## COOLING SYSTEM

Capacity: 6,5 liter (with automatic transmission), Capacity: 5,8 liter (with manual transmission)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Check every 7500 km/ 6 months, change every 30000 km/ 24 months

## AIRCONDITIONING SYSTEM

Capacity: 525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*