PEUGEOT (DONGFENG) 308S 308S 1.2 THP (2015 AND AFTER)



ENGINE EB2 Capacity: 3,5 liter, Filter capacity: 0,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Presteza MSP 0W-30	Duranza LSP 5W-30			
Change every 7500 km/ 6 months				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Helar 0W-40				
Change every 7500 km/ 6 months				

TRANSAXLE AUTOMATIC AT6 III 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Change every 90000 km/ 72 months	'			

TRANSAXLE MANUAL 5/1	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Change every 60000 km/ 48 months	

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Check every 7500 km/ 6 months, change every 24 months				

PRODUCT RECOMMENDATION

PEUGEOT (DONGFENG) 308S 308S 1.2 THP (2015 AND AFTER)



COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Charles arong 7500 km/s months, change arong 24 months		

Check every 7500 km/6 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.