## PEUGEOT (DONGFENG) 408 408 1.6 THP (2014 AND AFTER)



| ENGINE EP6 Capacity: 4,25 liter, Filter capacity: 0,25 liter |                          |          |  |  |
|--|--------------------------|----------|--|--|
| USE  |                          | CLIMATE  |  |  |
| Normal   |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1                                     | PRODUCT RECOMMENDATION 2 |          |  |  |
| Presteza MSP 0W-30   | Duranza LSP 5W-30        |          |  |  |
|  |                          |          |  |  |

Change every 7500 km/6 months

| TRANSAXLE AUTOMATIC AT6 III 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill) |          |  |
|--|----------|--|
| USE  | CLIMATE  |  |
| Severe   | Moderate |  |
| PRODUCT RECOMMENDATION 1   |          |  |
| SP Matic 4036  |          |  |
| Change every 90000 km/ 72 months   | '        |  |

| HYDRAULIC BRAKE SYSTEM    |                          |          |  |
|---------------------------|--------------------------|----------|--|
| USE                       |                          | CLIMATE  |  |
| Normal                    |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |  |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4       |          |  |

Check every 7500 km/6 months, change every 24 months

| COOLING SYSTEM  |          |  |
|---|----------|--|
| USE   | CLIMATE  |  |
| Normal  | Moderate |  |
| PRODUCT RECOMMENDATION 1                              |          |  |
| Coolant SP 14+  |          |  |
| Check every 7500 km/ 6 months, change every 24 months |          |  |

Check every 7500 km/6 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.