## **BESTURN (FAW) B90 B90 1.8T** (2014 AND AFTER)



<b>ENGINE</b> CA4GC18T Capacity: 4,8 liter, Filter capacity: 0,3	3 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Emperol 5W-40
Change every 10000 km/ 12 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Emperol 5W-40
Change every 5000 km/ 6 months		

TRANSAXLE AUTOMATIC F21 6/1 Capacity: 6,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 20000 km/ 12 months	'

use Normal		climate Moderate
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Check every 10000 km/ 6 months, cha	nge every 40000 km/24 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

## **BESTURN (FAW) B90 B90 1.8T** (2014 AND AFTER)



POWER STEERING Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 10000 km/ 6 months	

COOLING SYSTEM Capacity: 7,1-8,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant SP 12 EVO
Change every 40000 km/24 month	s	
USE		CLIMATE
First change only		Moderate

Coolant SP 15+	Coolant SP 12	Coolant SP 12 EVO
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
First change only		Moderate
USE		CLIMATE

Change every 60000 km/36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.