BESTURN (FAW) B90 B90 2.0 MT (2014 AND AFTER)

ENGINE CA4GD1
Capacity: 4,3 liter, Filter capacity: 0,4 liter

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40	

Change every 5000 km/ 6 months

TRANSAXLE MANUAL 6/1
Capacity: 2,95 liter

USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**		
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90		

Change every 60000 km/ 24 months

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90	

Change every 60000 km/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,7 liter

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	

Check every 10000 km/ 6 months, change every 12 months

BESTURN (FAW) B90 B90 2.0 MT (2014 AND AFTER)

POWER STEERING
Capacity: 0,9 liter

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			

Check every 10000 km/ 6 months

COOLING SYSTEM
Capacity: 7,1-8,1 liter

USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	Coolant SP 12	Coolant SP 12 EVO

Change every 40000 km/ 24 months

USE	CLIMATE	
First change only	Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	Coolant SP 12	Coolant SP 12 EVO

Change every 60000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.