HAIMA (FAW) M3 M3 1.5 MT HMA7150-DA4W/-DB4W/-DC4W (2014 AND AFTER)



ENGINE HMA GN15-VF Capacity: 3,6-3,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	

Change every 5000 km/6 months

TRANSAXLE MANUAL 6/1 Capacity: 1,8-2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change over 20000 km/24 month		·

Change every 20000 km/24 months

HYDRAULIC BRAKE/CLUTCH SYST Capacity: 0,57 liter	EM	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 20000 km/24 months		

POWER STEERING Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Check every 5000 km/6 months

COOLING SYSTEM Capacity: 4,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	

Check every 10000 km/ 10 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

HAIMA (FAW) M3 M3 1.5 MT HMA7150-DA4W/-DB4W/-DC4W (2014 AND AFTER)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.