TOYOTA (GAC) HIGHLANDER HIGHLANDER 2.0 T AWD (2015 AND AFTER)



USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 10000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Xedoz FE 5W-30
Change every 10000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Xedoz FE 5W-30
Change every 5000 km/ 6 months		
USE		CLIMATE
Preferred, severe		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
	·	·

Chook avany 20000	km/12	montho	ahanaa	01/0/1/	10000 km/10 months
CHECK EVELV ZUUUU	KIII/ 12	1110111115.	CHarlue	everv	40000 km/ 48 months

TRANSAXLE AUTOMATIC 6/1 Capacity: 6,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 40000 km/ 24 months				

Normal

SP Gear 1071

PRODUCT RECOMMENDATION 1

Moderate

PRODUCT RECOMMENDATION

TOYOTA (GAC) HIGHLANDER HIGHLANDER 2.0 T AWD (2015 AND AFTER)



TRANSFERBOX Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
Check every 20000 km/ 12 months, chang	e every 40000 km/ 48 months	
HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 10000 km/ 6 months, change	every 40000 km/ 24 months	
COOLING SYSTEM Capacity: 11,04 liter, Capacity: 3,56 liter (+	- intercooler)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 40000 km, change every 800	000 km	
LISE		CLIMATE

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

First change only

Coolant SP 14+

PRODUCT RECOMMENDATION 1

Check every 40000 km, change every 160000 km

Moderate