Change every 5000 km/6 months

## GEELY (GLEAGLE/ENGLON) HQ (HOAQING) HQ SRV (2003-2008)



<b>ENGINE</b> MR479Q Capacity: 3,5 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Bi-Turbo 15W-40	Bi-Turbo 20W-50			
Change every 5000 km/ 6 months				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Asyntho 5W-30	Emperol 10W-40			

TRANSAXLE MANUAL 4/1 Capacity: 2,25 liter (Initial fill), Capacity: 2,1 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Gearlube GL-4 80W-90				
Change every 40000 km/ 24 months	·			

HYDRAULIC BRAKE/CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 12 months	·

CLIMATE
Moderate
NDATION 2 PRODUCT RECOMMENDATION 3
ATF Dexron II-D

## GEELY (GLEAGLE/ENGLON) HQ (HOAQING) HQ SRV (2003-2008)



COOLING SYSTEM Capacity: 3,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 40000 km/ 24 months		·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.