## GEELY (GLEAGLE/ENGLON) ZIYOUJIAN ZYJ 1.3 (2007 AND AFTER)



ENGINE MR479Q Capacity: 3,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Bi-Turbo 15W-40	
Change every 7500 km/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Bi-Turbo 15W-40	
Change every 2000 km/2 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
Change every 40000 km/24 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 40000 km/24 months	6	·
USE		CLIMATE
nitial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
Change every 5000 km		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

## GEELY (GLEAGLE/ENGLON) ZIYOUJIAN ZYJ 1.3 (2007 AND AFTER)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,35 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 30000 km/ 12 months				

POWER STEERING Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Change every 40000 km/24 month	IS	

COOLING SYSTEM Capacity: 6,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 12 months		·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.