

GEELY (GLEAGLE/ENGLON) PANDA

PANDA 1.3 (2014 AND AFTER)



ENGINE MR479Q
Capacity: 3,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50*Change every 5000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Tropical

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50*Change every 3000 km/ 3 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 3000 km/ 3 months*

USE	CLIMATE
First change only	Tropical

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50*Change every 5000 km/ 3 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 5000 km/ 3 months*

GEELY (GLEAGLE/ENGLON) PANDA

PANDA 1.3 (2014 AND AFTER)

**TRANSAXLE AUTOMATIC 4/1**

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 40000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 5000 km/ 6 months

TRANSAXLE MANUAL 5/1

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		

Change every 40000 km/ 24 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Change every 40000 km/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 40000 km/ 24 months

GEELY (GLEAGLE/ENGLON) PANDA

PANDA 1.3 (2014 AND AFTER)



POWER STEERING

Capacity: 0,67 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 30000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.