JAC J6 / HEYUE J6 1.8 VVT (2013 AND AFTER)



| ENGINE 4G93D Capacity: 3,5 liter | | |
|-------------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 15W-40 | | |
| | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |

| TRANSAXLE AUTOMATIC 5/1 Capacity: 4,2-4,6 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4026 | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0,64-0,69 liter | | |
|---|---|---------------------|
| use Normal | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Drauliquid-LV Super DOT 4 | PRODUCT RECOMMENDATION 2 Drauliquid-S DOT 4 | |

| POWER STEERING Capacity: 1 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |

JAC J6 / HEYUE J6 1.8 VVT (2013 AND AFTER)



| COOLING SYSTEM Capacity: 6-7 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.