## PRODUCT RECOMMENDATION KIA (DYK) K2 UB K2 1.4 CVVT (2011-2014)



ENGINE G4FA Capacity: 3,7 liter (Dry fill), Capacity: 3,3 liter (Service fill), Filter capacity: 0,3 liter					
use Normal		CLIMATE			
		Mediterranean			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50			
Change every 5000 km/ 6 months	· ·	· · · ·			
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30			

Change every 5000 km/ 6 months

TRANSAXLE AUTOMATIC A4CF1 4/1 Capacity: 6,8 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 10000 km/ 12 months, change every 40000 km/ 48 months		

 TRANSAXLE MANUAL M6CF1 6/1

 Capacity: 1,8-1,9 liter

 use
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2

 SP Gear 5015
 Syngear 75W-90

Check every 10000 km/ 12 months, change every 30000 km/ 36 months

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,7-0,8 liter (Between min and max.)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3			

Check every 12 months

## KIA (DYK) K2 UB K2 1.4 CVVT (2011-2014)



POWER STEERING Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 5,3 liter, Capacity: 5,5 liter (with automatic transaxle)				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant SP 15+	Coolant SP 12			

Change every 12 months

## AIRCONDITIONING

Capacity: 445-495 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING COMPRESSOR Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.