TRANSAXLE AUTOMATIC A6MF1 6/1

# KIA (DYK) K5 TF K5 2.0 CVVL (2011-2015)



ENGINE G4NA Capacity: 4,8 liter (Dry fill), Capacity: 4,	1 liter (Service fill)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50
Change every 5000 km/ 6 months	·	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30
Change every 5000 km/ 6 months	·	
USE		CLIMATE
First change only		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50
Change every 7500 km/ 6 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30
	· ·	<del></del>

Capacity: 7,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 10000 km/ 12 months, chang	re every 40000 km/ 48 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 12500 km/ 12 months, change	ne every 42500 km/ 48 months	

HYDRAULIC BRAKE/CLUTCH SYSTEM

## KIA (DYK) K5 TF K5 2.0 CVVL (2011-2015)



TRANSAXLE MANUAL M6CF4 6/1 Capacity: 1,8-1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 10000 km/ 12 months, ch	ange every 30000 km/ 36 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 12500 km/ 12 months, ch	ange every 32500 km/ 36 months	

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Check every 5000 km/ 6 months		
USE		CLIMATE
First check only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Drauliquid-S DOT 4	Drauliquid DOT 3

Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 5000 km/ 6 months	
USE	CLIMATE
First check only	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 7500 km/ 6 months	

**POWER STEERING** 

### KIA (DYK) K5 TF K5 2.0 CVVL (2011-2015)



COOLING SYSTEM Capacity: 6,5-6,6 liter		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 12 months	·	

### **AIRCONDITIONING**

We are unable to give a standard recommendation for this component. Please contact our service department.

### AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.