

KIA (DYK) K5 TF K5 2.0 CVVT HYBRID (2012 AND AFTER)

**ENGINE** Nu HEV 2.0

Capacity: 4,5 liter (Dry fill), Capacity: 4 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 7500 km/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30

Change every 7500 km/ 6 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 5000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30

Change every 5000 km/ 6 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service, severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 7500 km/ 6 months

PRODUCT RECOMMENDATION

KIA (DYK) K5 TF K5 2.0 CVVT HYBRID (2012 AND AFTER)



USE		CLIMATE
Initial service, severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30
<i>Change every 7500 km/ 6 months</i>		

TRANSAXLE AUTOMATIC A6MF2H 6/1 Capacity: 6,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
<i>Check every 15000 km/ 12 months, change every 60000 km/ 48 months</i>		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
<i>Check every 10000 km/ 12 months, change every 40000 km/ 48 months</i>		

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
<i>Change every 30000 km/ 24 months</i>		

POWER STEERING Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		



KIA (DYK) K5 TF K5 2.0 CVVT HYBRID (2012 AND AFTER)



COOLING SYSTEM

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 12 months

AIRCONDITIONING

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.