

LIFAN 620 / SOLANO 620 / SOLANO 1.5

(2010 AND AFTER)



ENGINE LF479Q2
Capacity: 3-3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Bi-Turbo 15W-40

Change every 8000 km

TRANSAXLE MANUAL 5/1
Capacity: 2-2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		

Change every 90000 km/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,72 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 50000 km/ 24 months

POWER STEERING
Capacity: 0,83 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM
Capacity: 5,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

LIFAN 620 / SOLANO 620 / SOLANO 1.5 **(2010 AND AFTER)**



information contained herein is subject to changes without notification.