## **PORSCHE (CHN) 911 964 911 CARRERA 997** (2004 AND AFTER)



<b>ENGINE</b> M 96/05 Capacity: 8,25 liter, Filter capacity: 0,25 lit	er	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Helar 0W-40	Emperol 5W-40

Change every 10000 km/ 12 months

DIFFERENTIAL FROM AUTOMAT Capacity: 1,2 liter	TIC		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
0//400			

Change every 180000 km/ 120 months

TRANSAXLE MANUAL 6/1 Capacity: 2,9 liter (Dry fill), Capacity	y: 2,6 liter (Service fill)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
		<del></del>	

Change every 180000 km/ 120 months

TRANSMISSION AUTOMATIC Tiptronic S 5/1 Capacity: 9 liter (Dry fill), Capacity: 4,5 liter (Service fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Change every 180000 km/ 120 months	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,45 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Check every 24 months/ 30000 km	·

## **PORSCHE (CHN) 911 964 911 CARRERA 997** (2004 AND AFTER)



POWER STEERING Capacity: 1,27 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 24 months/ 30000 km	

COOLING SYSTEM Capacity: 32 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 24 months/ 30000 km	'	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.