

WULING (SGMW) SPARK SPARK 0.8 SOHC

(2008 AND AFTER)

**ENGINE**

Capacity: 2,7 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Change every 10000 km/ 6 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40*Change every 10000 km/ 6 months***TRANSMISSION MANUAL 5/1**

Capacity: 2,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Change every 40000 km*

USE

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Change every 10000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,45 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

WULING (SGMW) SPARK SPARK 0.8 SOHC (2008 AND AFTER)

**POWER STEERING**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.