

BRILLIANCE FRV/BS2 FRV / BS2 / CROSS

1.5 (75 KW) SY7150WSBAA (2011 AND AFTER)



ENGINE 4A15
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 5000 km*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 5000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 2500 km*

USE	CLIMATE
Severe	Cold

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 2500 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 2000 km*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 2000 km*

USE	CLIMATE
Initial service, severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 1000 km*

BRILLIANCE FRV/BS2 FRV / BS2 / CROSS 1.5 (75 KW) SY7150WSBAA (2011 AND AFTER)



USE		CLIMATE
Initial service, severe		Cold
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		
<i>Change every 1000 km</i>		

TRANSAXLE MANUAL 5/1 Capacity: 1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
<i>Check every 20000 km, change every 40000 km</i>		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
<i>Check every 10000 km, change every 30000 km</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
<i>Check every 6000 km, change every 10000 km</i>		



BRILLIANCE FRV/BS2 FRV / BS2 / CROSS 1.5 (75 KW) SY7150WSBAA (2011 AND AFTER)



HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE	CLIMATE
Severe, first change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 5000 km/ 3 months

BRILLIANCE FRV/BS2 FRV / BS2 / CROSS 1.5 (75 KW) SY7150WSBAA (2011 AND AFTER)

**POWER STEERING**

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 10000 km/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 5000 km/ 3 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.