

KIA (DYK) SPORTAGE SL SPORTAGE 2.0

(2010 AND AFTER)



ENGINE G4GC
Capacity: 4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 7500 km/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Change every 7500 km/ 6 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 5000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Change every 5000 km/ 6 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service, severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 7500 km/ 6 months

KIA (DYK) SPORTAGE SL SPORTAGE 2.0 (2010 AND AFTER)



USE		CLIMATE
Initial service, severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40
<i>Change every 7500 km/ 6 months</i>		

TRANSAXLE AUTOMATIC 4/1 Capacity: 7,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
<i>Check every 15000 km/ 12 months, change every 60000 km/ 48 months</i>		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
<i>Check every 10000 km/ 12 months, change every 40000 km/ 48 months</i>		

TRANSAXLE MANUAL 5/1 Capacity: 2,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
<i>Check every 15000 km/ 12 months, change every 45000 km/ 36 months</i>		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
<i>Check every 10000 km/ 12 months, change every 30000 km/ 36 months</i>		

HYDRAULIC BRAKE SYSTEM Capacity: 0,7-0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
<i>Change every 5000 km/ 6 months</i>		

KIA (DYK) SPORTAGE SL SPORTAGE 2.0 (2010 AND AFTER)



POWER STEERING

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 5000 km/ 6 months*

COOLING SYSTEM

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Change every 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.