

CASE - IH CS CS 130 (1998 AND AFTER)

ENGINE WD 620.82
Capacity: 20 liter

USE Normal		CLIMATE Mediterranean
----------------------	--	---------------------------------

PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 20W-50	PRODUCT RECOMMENDATION 3 Multifleet SCD 40
--	--	---

Check every 10 hours, change every 250 hours/ 12 months

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40
--	--	--

Check every 10 hours, change every 250 hours/ 12 months

USE Normal		CLIMATE Arctic
----------------------	--	--------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
--	--	--

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 6,2 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 2 Agrifluid HT	PRODUCT RECOMMENDATION 3 Gearlube GL-5 80W-90
---	--	--

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,5 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 2 Agrifluid HT	PRODUCT RECOMMENDATION 3 Gearlube GL-5 80W-90
---	--	--

Check every 500 hours, change every 1000 hours/ 12 months

CASE - IH CS CS 130 (1998 AND AFTER)**HUB REDUCTIONS REAR**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

*Check every 500 hours, change every 1000 hours/ 12 months***TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 40/40**

Capacity: 76 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	

*Check every 500 hours, change every 1000 hours/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

*Check every 50 hours, change every 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

*Change every 50 hours***COOLING SYSTEM**

Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2400 hours

CASE - IH CS CS 130 (1998 AND AFTER)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.