CASE - IH CVX CVX1145 (2003-2006)



| ENGINE Capacity: 20 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Extended | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 |
| Check every 10 hours, change every 500 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Multifleet SHPD 10W-40 |

Check every 10 hours, change every 250 hours/ 12 months

| DIFFERENTIAL FRONT Capacity: 2,2 liter (20.25 suspension | n), Capacity: 5,5 liter (20.29 suspension), Capac | ity: 8 liter (Standard) |
|---|---|-------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check every 12 months/ 500 hours | change every 1000 hours/24 months | • |

| USE | | CLIMATE |
|--------------------------|-----------------------------|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 250 hours/ 6 months

| HUB REDUCTIONS FRONT (4X4) + BRAKES Capacity: 2 liter | | |
|--|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |
| Check every 250 hours, change every 500 hours/ 12 months | | |
| USE | CLIMATE | |
| First change only | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |
| Change every 250 hours/ 6 months | | |
| | | |

Change every 250 hours/ 6 months

CASE - IH CVX CVX1145 (2003-2006)



| HUB REDUCTIONS FRONT (4X4) WITHOUT BRAKES Capacity: 1,5 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check every 250 hours, change every 500 hours/ 12 months | | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

| HUB REDUCTIONS REAR Capacity: 10 liter | | |
|--|----------------------------------|------------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Gearlube Racing 75W-140 | Gearlube LS 80W-90 | Unigear LS GL-3/GL-5 85W-140 |
| Check every 12 months / 500 hours of | hange eveny 1000 hours/24 months | ' |

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

| POWER TAKE OFF FRONT Capacity: 3 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Kroontrak MTH 10W-30 | |
| Check every 10 hours, change every 100 hours | · |

| TRANSMISSION AUTOMATIC 1/1 Capacity: 60 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Kroontrak CVT 10W-40 | |
| Check every 10 hours, change every 1000 hours/24 | months |

Check every 10 hours, change every 1000 hours/24 months

CASE - IH CVX CVX1145 (2003-2006)



| HYDRAULIC SYSTEM POWER ST Capacity: 52 liter | TEERING | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| ATF Dexron II-D | Perlus H 46 | Perlus AF 46 |
| | · | · |

Check every 250 hours, change every 1000 hours/12 months

| HYDRAULIC BRAKE SYSTEM Capacity: 0,75 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| LHM + | |
| | |

Check every 10 hours, change every 2000 hours/24 months

| COOLING SYSTEM Capacity: 25 liter | | |
|-----------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |
| Check every 10 hours, change eve | ary 1000 hours/12 months | |

Check every 10 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.