## **CASE - IH PUMA CVX/CVT PUMA 230 CVX** (2013-2015)



ENGINE Capacity: 15 liter		
USE		CLIMATE
Normal, fuel sulfur level < 500 ppm		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 600 hours

DIFFERENTIAL FRONT Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT
Check every 300 hours, change every	/ 1200 hours/ 12 months	·

HUB REDUCTIONS FRONT
Capacity: 3,8 liter (With brakes), Capacity: 2,3 liter (Without brakes)

USE

Normal

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

Agrifluid HT

Check every 300 hours, change every 1200 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 3,05 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT
Check every 10 hours, change every	600 hours	

TRANSMISSION AUTOMATIC 1/1
Capacity: 84 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

Check every 300 hours, change every 1200 hours/ 12 months

Capacity: 84 liter

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus

Agrifluid HT

## **CASE - IH PUMA CVX/CVT PUMA 230 CVX** (2013-2015)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	•	•

COOLING SYSTEM Capacity: 22,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 10 hours, change every 1200 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.