

# CASE - IH QUANTUM C QUANTUM C65 (2008-2014)

**ENGINE** Tier III

Capacity: 9,5 liter, Filter capacity: 0,6 liter

| USE                          |                               | CLIMATE                       |
|------------------------------|-------------------------------|-------------------------------|
| Normal                       |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Multifleet SHPD 10W-40</b> |

**DIFFERENTIAL FRONT**

Capacity: 4,5 liter

| USE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |

**HUB REDUCTIONS FRONT**

Capacity: 1,5 liter (+ front brakes), Capacity: 1 liter (Without brakes)

| USE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |

**POWER TAKE OFF FRONT**

Capacity: 0,5 liter

| USE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |

**TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING**

Capacity: 42 liter

| USE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |

# CASE - IH QUANTUM C QUANTUM C65

(2008-2014)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0,7-1 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>LHM +</b>             |  |          |

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM

Capacity: 14 liter, Capacity: 16 liter (+ cabin)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.