

# CASE - IH STX STX 275 / STX 275 ACCUSTEER (2000 AND AFTER)



**ENGINE** CDC 6TAA-8304  
Capacity: 23,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel CRD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Asyntho 5W-30</b>	<b>Armado Synth 5W-30</b>

*Check every 10 hours, change every 250 hours*

## DIFFERENTIAL FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

*Change every 1500 hours/ 12 months*

## DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

*Change every 1500 hours/ 12 months*

## REDUCTION UNITS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

*Change every 1500 hours/ 12 months*

# CASE - IH STX STX 275 / STX 275 ACCUSTEER (2000 AND AFTER)



## REDUCTION UNITS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		
<i>Change every 1500 hours/ 12 months</i>		

## TRANSMISSION MANUAL/P.T.O.

Capacity: 76 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		
<i>Check every 10 hours, change every 1500 hours</i>		

## HYDRAULIC SYSTEM

Capacity: 178 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		
<i>Check every 10 hours, change every 1500 hours</i>		

## COOLING SYSTEM

Capacity: 43 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	
<i>Check every 10 hours, change every 24 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.