

CLAAS ARES 600 ARES 626 (H8222) (2003-2009)

**ENGINE 6068 TRT53**

Capacity: 17 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Check every 10 hours, change every 300 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 100 hours***DIFFERENTIAL FRONT A 88-1**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 300 hours, change every 1200 hours/ 12 months***DIFFERENTIAL FRONT ProActiv 2043 SI**

Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 300 hours, change every 1200 hours/ 12 months***HUB REDUCTIONS FRONT**

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 300 hours, change every 600 hours/ 12 months*

CLAAS ARES 600 ARES 626 (H8222) (2003-2009)



POWER TAKE OFF FRONT

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 50 hours, change every 600 hours*

TRANSMISSION/HYDRAULIC SYSTEM

Capacity: 65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 10 hours, change every 1200 hours/ 12 months*

HYDRAULIC BRAKE SYSTEM

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

LHM +*Check every 10 hours, change every 1200 hours/ 12 months*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 2

MP Lithep Grease EP 2*Check every 50 hours*

COOLING SYSTEM

Capacity: 16,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 10 hours, change every 1500 hours/ 24 months*

CLAAS ARES 600 ARES 626 (H8222) (2003-2009)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.