CLAAS ARION ARION 530 TIER 3A/B (2008-2012)



ENGINE DPS Capacity: 10-12,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT Capacity: 6 liter (Standard), Capacity: 2,2 liter (Suspended front axle)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 10 hours, change every 1000 hours		

HUB REDUCTIONS FRONT Capacity: 0,6 liter (Standard), Capacity: 1,5 liter (Suspended front axle)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 10 hours, change every 1000 hours		

TRANSMISSION/HYDRAULIC SYSTEM Capacity: 63 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 10 hours, change every 1000 hours

CLIMATE
Moderate

CLAAS ARION ARION 530 TIER 3A/B (2008-2012)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 17,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	ery 2000 hours/ 24 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.