

CLAAS AXION AXION 820 CMATIC (2008-2014)

**ENGINE DPS**

Capacity: 22-25 liter

USE		CLIMATE
Normal, fuel sulfur level < 0,2 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal, fuel sulfur level > 0,2 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

*Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT**

Capacity: 12 liter (Standard), Capacity: 12 liter (Suspended front axle)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

*Check every 1 months/ 100 hours, change every 1000 hours***HUB REDUCTIONS FRONT**

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

*Check every 200 hours, change every 1000 hours***POWER TAKE OFF FRONT**

Capacity: 1,3-1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 50 hours, change every 6 months/ 500 hours

CLAAS AXION AXION 820 CMATIC (2008-2014)



TRANSMISSION CMATIC

Capacity: 44 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus*Check every 50 hours, change every 1000 hours/ 24 months*

HYDRAULIC SYSTEM

Capacity: 104 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus*Check every 10 hours, change every 1000 hours*

HYDRAULIC BRAKE SYSTEM

Capacity: 0,9 liter (40 km/h version)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

LHM +*Check every 10 hours, change every 2000 hours/ 24 months*

GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50 hours*

COOLING SYSTEM

Capacity: 27 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 16*Check every 10 hours, change every 1500 hours/ 24 months*

CLAAS AXION AXION 820 CMATIC (2008-2014)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.