

# CLAAS AXION AXION 930 STAGE II A23 / B06

**ENGINE FPT**

Capacity: 19,5-27,5 liter

**USE**

Normal, fuel sulfur level &lt; 0,2 %

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agrisynth LSP Ultra FE 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 5W-30****PRODUCT RECOMMENDATION 3****Armado Synth 5W-30***Check every 10 hours, change every 600 hours/ 12 months***DIFFERENTIAL FRONT**

Capacity: 15 liter (Standard), Capacity: 14 liter (Suspended front axle)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 1200 hours***HUB REDUCTIONS FRONT**

Capacity: 5 liter (With brakes), Capacity: 6 liter (Without brakes)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 1200 hours***USE**

With brakes

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 600 hours***POWER TAKE OFF FRONT**

Capacity: 3,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 50 hours, change every 600 hours/ 12 months*

# CLAAS AXION AXION 930 STAGE II A23 / B06



## TRANSMISSION/HYDRAULIC SYSTEM

Capacity: 155-165 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

Check every 10 hours, change every 1800 hours

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Change every 50 hours

## GREASE POINTS/NIPPLES FRONT AXLE POINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Labora Grease</b>		

## COOLING SYSTEM

Capacity: 40 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 10 hours, change every 24 months/ 1800 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.