

COUNTY ALL MODELS 774 (1982-1991)**ENGINE Ford 6610**

Capacity: 9,5 liter, Filter capacity: 0,9 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 10 hours, change every 300 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40*Check every 10 hours, change every 300 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 10 hours, change every 300 hours***DRIVE SHAFT HOUSING**

Capacity: 0,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3

Gearlube HS GL-5 80W-140*Check every 300 hours, change every 1200 hours/ 12 months***REDUCTION UNITS FRONT**

Capacity: 4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3

Gearlube HS GL-5 80W-140*Check every 50 hours, change every 1200 hours/ 12 months*

COUNTY ALL MODELS 774 (1982-1991)**REDUCTION UNITS REAR**

Capacity: 6 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|---------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | Gearlube HS GL-5 80W-140 |

*Check every 50 hours, change every 1200 hours/ 12 months***TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 61,8 liter

| USE | | CLIMATE |
|-----------------------------|-----------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Kroontrak MTH 10W-30 | Agrifluid HT |

*Check every 50 hours, change every 1200 hours/ 12 months***POWER STEERING**

Capacity: 2,3 liter

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 10W | ATF-A | |

*Check every 300 hours, change every 600 hours***GREASE POINTS/NIPPLES CLUTCH RELEASE BEARING**

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES OTHERS

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

COUNTY ALL MODELS 774 (1982-1991)**COOLING SYSTEM**

Capacity: 18,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 11****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 1200 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.